

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 April 2004 (01.04.2004)


PCT

(10) International Publication Number  
**WO 2004/027321 A1**

- (51) International Patent Classification<sup>7</sup>: **F24C 7/00**
- (21) International Application Number: **PCT/EP2003/010465**
- (22) International Filing Date:  
19 September 2003 (19.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0221728.9 19 September 2002 (19.09.2002) GB  
0313057.2 6 June 2003 (06.06.2003) GB
- (71) Applicant (for all designated States except US): **BASIC HOLDINGS [IE/IE]**; 41 Ailesbury Road, Dublin 4 (IE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **O'NEILL, Noel [IE/IE]**; 30 Riverview, Mell, Drogheda, Co Louth (IE).
- (74) Agent: **HARRISON GODDARD FOOTE**; Belgrave Hall, Belgrave Street, Leeds LS2 8DD (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: APPARATUS FOR PROVIDING A VISUAL EFFECT



(57) **Abstract:** Apparatus for simulating flames and such apparatus used in a wall-mounted flame effect electric fire are described. The apparatus arranges a light source below a reflecting means and a means for modifying light from the light source in front of the light source and below a partially diffusing and partially transmitting viewing screen. The light source comprises at least one halogen bulb or other lamp of comparable power, brightness size and intensity. The fire incorporating the flame simulating apparatus arranges a fan heater to draw air in through, and to expel heated air through, the base of the fire. The arrangement reduces the depth of the fire to facilitate wall mounting.

WO 2004/027321 A1

WO 2004/027321 A1



**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*